

轴径	型号	主要尺寸					靠肩尺寸		基本额定负荷 (径向)		重量
		内径 d (mm)	外径 D (mm)	滚子节 圆直径	宽度 B (mm)	倒角 r (mm)	ds (mm)	Dh (mm)	C KN	Co KN	kg
20	RU42	20	70	41.5	12	0.6	37	47	7.35	8.35	0.29
35	RU66	35	95	66	15	0.6	59	74	17.5	22.3	0.62
55	RU85	55	120	85	15	0.6	79	93	20.3	29.5	1
80	RU124G	80	165	124	22	1	114	134	33.1	50.9	2.6
	RU124X										
90	RU148G	90	210	147.5	25	1.5	133	162	49.1	76.8	4.9
	RU148X										
115	RU178G	115	240	178	28	1.5	161	195	80.3	135	6.8
	RU178X										
160	RU228G	160	295	227.5	35	2	208	246	104	172	11.4
	RU228X										
210	RU297G	210	380	297.3	40	2.5	272	320	156	281	21.3
	RU297X										
350	RU445G	350	540	445.4	45	2.5	417	473	222	473	35.4
	RU445X										

轴径	型号	主要尺寸					靠肩尺寸		基本额定负荷 (径向)		重量
		内径 d (mm)	外径 D (mm)	滚子节 圆直径	宽度 B (mm)	倒角 r (mm)	ds (mm)	Dh (mm)	C KN	Co KN	kg
20	RU42	20	70	41.5	12	0.6	37	47	7.35	8.35	0.29
35	RU66	35	95	66	15	0.6	59	74	17.5	22.3	0.62
55	RU85	55	120	85	15	0.6	79	93	20.3	29.5	1
80	RU124G	80	165	124	22	1	114	134	33.1	50.9	2.6
	RU124X										
90	RU148G	90	210	147.5	25	1.5	133	162	49.1	76.8	4.9
	RU148X										
115	RU178G	115	240	178	28	1.5	161	195	80.3	135	6.8
	RU178X										
160	RU228G	160	295	227.5	35	2	208	246	104	172	11.4
	RU228X										
210	RU297G	210	380	297.3	40	2.5	272	320	156	281	21.3
	RU297X										
350	RU445G	350	540	445.4	45	2.5	417	473	222	473	35.4
	RU445X										